

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LuxaPrint Gingiva

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Manufacture of plastics products, including compounding and conversion

Uses advised against

Do not use for sputtering or spraying.

Avoid: generation/formation of aerosols

1.3. Details of the supplier of the safety data sheet

Company name:	DMG America LLC
Street:	242 South Dean Street
Place:	Englewood, NJ 07631
Telephone:	(800) 662-6383
e-mail:	info@dmg-america.com
Internet:	www.dmg-america.com

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1A

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Toxic if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate

EBPADMA

Decandiol dimethacrylate

EBPADMA

1-(morpholin-4-yl)prop-2-en-1-one

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Phenyl-bis(2,4,6-trimethylbenzoyl)-phosphinoxide

Tri-ethylenglycol-dimethacrylate (TEDMA)

Signal word: Danger**Pictograms:**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 2 of 9

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P321	Specific treatment (see ... on this label).
P332	If skin irritation occurs:
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a POISON CENTER/doctor.
P321	Specific treatment (see ... on this label).
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to ...

Special labelling of certain mixtures

30 - < 35 % of the mixture consists of ingredient(s) of unknown acute toxicity (oral).
 60 - < 65 % of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).
 55 - < 60 % of the mixture consists of ingredient(s) of unknown acute toxicity (inhalation).
 Contains 30 - < 35 % of components with unknown hazards to the aquatic environment.
 Restricted to professional users.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 3 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
63225-53-6	2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate			10-20 %
	264-036-0		01-2120751208-56	
	Acute Tox. 3, Skin Sens. 1A, Aquatic Chronic 2; H331 H317 H411			
41637-38-1	EBPADMA			10-20 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			
6701-13-9	Decandiol dimethacrylate			5-10 %
	229-745-1		01-2120735533-57	
	Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
41637-38-1	EBPADMA			5-10 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			
5117-12-4	1-(morpholin-4-yl)prop-2-en-1-one			2-5 %
	418-140-1		01-0000016491-73	
	Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, STOT RE 2; H302 H318 H317 H373			
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			0,5-2 %
	278-355-8		01-2119972295-29	
	Repr. 2, Skin Sens. 1, Aquatic Chronic 2; H361f H317 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixtureCO_x, NO_x**SECTION 6: Accidental release measures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 4 of 9

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	WEL
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
1309-37-1	Iron oxide, fume (as Fe)	-	5		TWA (8 h)	WEL
		-	10		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
109-16-0	Tri-ethylenglycol-dimethacrylate (TEDMA)			
Worker DNEL, long-term		inhalation	systemic	48,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	13,9 mg/kg bw/day

PNEC values

CAS No	Substance	Value
109-16-0	Tri-ethylenglycol-dimethacrylate (TEDMA)	
Freshwater		0,164 mg/l
Marine water		0,0164 mg/l
Freshwater sediment		1,85 mg/kg
Marine sediment		0,185 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,274 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 5 of 9

8.2. Exposure controls**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:

Colour:

Changes in the physical state**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

Light. heat.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalation vapour) 8,68 mg/l; ATE (inhalation aerosol) 1,446 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
63225-53-6	2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate				
	oral	LD50 > 2000 mg/kg	rattus	supplier MSDS	
	dermal	Data lacking			
	inhalation (4 h) vapour	LC50 3 mg/l	rattus	supplier MSDS	
	inhalation aerosol	ATE 0,5 mg/l			
6701-13-9	Decandiol dimethacrylate				
	oral	LD50 > 2000 mg/kg	rattus	supplier MSDS	OECD 401
	dermal	Data lacking			
	inhalation	Data lacking			
5117-12-4	1-(morpholin-4-yl)prop-2-en-1-one				
	oral	LD50 588 mg/kg	rattus	supplier MSDS	
	dermal	LD50 > 2000 mg/kg	rattus	supplier MSDS	
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 > 5000 mg/kg	Rat	SDS	
	dermal	LD50 > 2000 mg/kg	Rat	SDS	
	inhalation	Data lacking			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
63225-53-6	2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate					
	Acute fish toxicity	LC50 mg/l	2,52	96 h	B. rerio	supplier MSDS
	Acute algae toxicity	ErC50 mg/l	5,98	72 h	D. subspicatus	supplier MSDS
	Acute bacteria toxicity	(305 mg/l)		3 h	activated sludge	supplier MSDS
41637-38-1	EBPADMA					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	(indet)	supplier MSDS
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	(indet)	supplier MSDS
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	D. magna	supplier MSDS
6701-13-9	Decandiol dimethacrylate					
	Acute fish toxicity	LC50 mg/l	0,1489	96 h	D. rerio	supplier MSDS read across
	Acute algae toxicity	ErC50 mg/l	0,014	72 h	P. subcapitata	supplier MSDS OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,3084	48 h	D. magna	supplier MSDS read across
41637-38-1	EBPADMA					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	(indet)	supplier MSDS
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	(indet)	supplier MSDS
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	D. magna	supplier MSDS
5117-12-4	1-(morpholin-4-yl)prop-2-en-1-one					
	Acute algae toxicity	ErC50	120 mg/l	72 h	algae	supplier MSDS
	Acute crustacea toxicity	EC50	120 mg/l	48 h	D. magna	supplier MSDS
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute fish toxicity	LC50 mg/l	6,53	96 h	Oryzias latipes (Ricefish)	SDS
	Acute algae toxicity	ErC50 mg/l	> 2,01	72 h	Scenedesmus subspicatus	SDS
	Acute crustacea toxicity	EC50 mg/l	3,53	48 h	Daphnia magna (Big water flea)	SDS
	Acute bacteria toxicity	(> 1000 mg/l)		3 h	Activated sludge	SDS

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
63225-53-6	2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate			
	Biodegradation (water)	15 %	28	
6701-13-9	Decandiol dimethacrylate			
	OECD 301F	86,6%	28	supplier MSDS
	not easily biologically degradable			

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 8 of 9

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
6701-13-9	Decandiol dimethacrylate	> 6,5
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 2810
14.2. UN proper shipping name:	TOXIC LIQUID, ORGANIC, N.O.S (contains 2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate)
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III

Marine transport (IMDG)

14.1. UN number:	UN 2810
14.2. UN proper shipping name:	TOXIC LIQUID, ORGANIC, N.O.S (contains 2-[[[(Butylamino)carbonyl]oxy]ethyl acrylate)
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III
EmS:	F-A, S-A

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 3 - strongly hazardous to water

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Gingiva

Revision date: 05.08.2020

Product code: 171278, 171240, 171241

Page 9 of 9

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 3; H331	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1A; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)