

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 1 of 6

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Ecosite Bond

Product group: dprodukt

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company Name: DMG America LLC  
Address: 242 South Dean Street  
City, State, Zip Code: Englewood, NJ. 07631  
Telephone: (800) 662 - 6383  
Email: [Info@dmg-america.com](mailto:Info@dmg-america.com)  
Website: [www.dmg-america.com](http://www.dmg-america.com)

INFOTRAC Emergency No. (800) 535-5053

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Hazard Statements:

Flammable liquid and vapour.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



##### Hazard statements

H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

##### Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P233 Keep container tightly closed.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 2 of 6

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64-17-5	ethanol, ethyl alcohol			10 - 50 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2; H225			
868-77-9	2-hydroxyethyl methacrylate			20 - 30 %
	212-782-2	607-124-00-X		
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1; H319 H315 H317			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

#### Unsuitable extinguishing media

High power water jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation. Remove all sources of ignition. Keep away from heat.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Collect mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

#### Advice on protection against fire and explosion

Keep away from heat. Keep away from sources of ignition - No smoking.

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 3 of 6

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

### 8.2. Exposure controls



#### Appropriate engineering controls

Ventilate affected area.

#### Protective and hygiene measures

When using do not eat or drink.

#### Eye/face protection

Tightly sealed safety glasses.

#### Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

#### Respiratory protection

The following must be prevented: inhalation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
Colour: yellow  
Odour: like: ester

#### Test method

pH-Value (at 23 °C): 4,5

#### Changes in the physical state

Initial boiling point and boiling range: 78 °C

point of decomposition: 200 °C

Flash point: 24 °C DIN EN ISO 2719

Density: 1,1 g/cm<sup>3</sup>

Water solubility: 60 % g/L

## SECTION 10: Stability and reactivity

### 10.4. Conditions to avoid

heat. Light.

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 4 of 6

Decomposition takes place from temperatures above: 200°C

### 10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

### 10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

### Further information

Substances sensitive to light.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Warning - substance not yet tested completely.

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
64-17-5	ethanol, ethyl alcohol				
	oral	LD50	6200 mg/kg	Rat	IUCLID
	inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50	5050 mg/kg	Rat	

#### Irritation and corrosivity

Irritant effect on the eye:

Frequently or prolonged contact with skin may cause dermal irritation.

#### Sensitising effects

May cause sensitization by skin contact.

#### Specific effects in experiment on an animal

LD50: Rat. 2.000mg/kg

#### Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product is partially biodegradable. >50 %

Acute fish toxicity LC50: >230 mg / l / 96 h

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
64-17-5	ethanol, ethyl alcohol				
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h Daphnia magna	IUCLID
868-77-9	2-hydroxyethyl methacrylate				
	Acute fish toxicity	LC50	227 mg/l	96 h Pimephales promelas	

### 12.3. Bioaccumulative potential

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 5 of 6

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31
868-77-9	2-hydroxyethyl methacrylate	0,47

### Further information

Do not empty into drains or the aquatic environment. Leakage into the environment must be prevented.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Carry out a burning of hazardous waste according to official regulations.

#### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances  
Classified as hazardous waste.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 144 601  
Limited quantity: 5 L  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

#### Other applicable information (land transport)

E1

### Marine transport (IMDG)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: 144, 223  
Limited quantity: 5 L

# Safety Data Sheet

## Ecosite Bond

Product code: 222758 (2226)

Page 6 of 6

EmS: F-E, S-D

### Other applicable information (marine transport)

E1

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A58 A180  
Limited quantity Passenger: 10 L  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

### Other applicable information (air transport)

E1  
: Y344

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

## SECTION 16: Other information

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

*(The data for the hazardous ingredients were taken respectively from the last version (10/04/2017) of the sub-contractor's safety data sheet.)  
According to Regulation GHS\_OSHA\_(EC) No. 1907/2006*